Material Safety Data Sheet According to 91/155 EEC

Printing date 06.07.2006 Reviewed on 15.07.2005 1 Identification of substance/preparation and the company /undertaking: * Product details: * Trade name: DECOMET 3108/10 * Application of the substance / the preparation metallic pigment for paints, printing inks and plastics * Manufacturer/Supplier: Schlenk Metallpulver GmbH&Co KG Tel.: ++49/9171/808-0 Barnsdorfer Hauptstr.5 Fax.: ++49/9171/808200 D-91154 Roth-Barnsdorf *Informing department: Tel.: ++49/9171/808320 Department QSI Fax: ++49/9171/808208 *Emergency information: ++49/9171/808-0 2 Composition/Data on ingredients: * Chemical characterization * Description: Mixture of the substances listed below with harmless additions. *Dangerous components: CAS: 108-65-6 2-methoxy-1-methylethyl acetate 🗙 Xi; R 10-36 70-90% EINECS: 203-603-9 CAS: 7429-90-5 aluminium powder (stabilized) 🗼 F; R 10-15 10-30% EINECS: 231-072-3 3 Hazards identification *Hazard designation: Xi Irritant * Information pertaining to particular dangers for man and environment R 10 Flammable. R 36 Irritating to eves. [•]Classification svstem The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

4 First aid measures

* After inhalation Supply fresh air; consult doctor in case of symptoms.

- * After skin contact The product is not skin irritating.
- * After eye contact
- Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- * After swallowing Seek medical treatment.

5 Fire fighting measures

- * Suitable extinguishing agents
- Alcohol-resistant foam

Use fire fighting measures that suit the environment.

(Contd. on page 2)

GB

Material Safety Data Sheet According to 91/155 EEC

Printing date 06.07.2006

Trade name: DECOMET 3108/10

(Contd. of page 1)

* Protective equipment:

Wear self-contained breathing apparatus. Wear full protective suit.

6 Accidental release measures

* **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away. * **Measures for environmental protection:**

Prevent material from reaching sewage system, holes and cellars.

Do not allow to enter drainage system, surface or ground water.

* Measures for cleaning/collecting: Do not flush with water or aqueous cleansing agents

* Additional information: See Section 7 for information on safe handling

7 Handling and storage

*Handling

- * *Information for safe handling:* Store in cool, dry place in tightly closed containers. * *Information about protection against explosions and fires:*
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.

* Storage

- * Requirements to be met by storerooms and containers: No special requirements.
- * Information about storage in one common storage facility: Not required.
- * Further information about storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

8 Exposure controls and personal protection

* Additional information about design of technical systems: No further data; see item 7.

* Components with critical values that require monitoring at the workplace:

7429-90-5 aluminium powder (stabilized)

OEL Short-term value: 5 mg/m3

Long-term value: 5 mg/m3

* Additional information: The lists that were valid during the compilation were used as basis.

* Personal protective equipment

* General protective and hygienic measures

Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

* Breathing equipment: Not required.

* Protection of hands: Not mandatory.

* Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

* Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 3)

Material Safety Data Sheet According to 91/155 EEC

Printing date 06.07.2006

Reviewed on 15.07.2005

Trade name: DECOMET 3108/10

(Contd. of page 2)

* Eye protection: Tightly sealed safety glasses. * Skin protection: Protective work clothing.

*General Information	
Form:	Fluid
Colour: Smell:	Silver grey Characteristic
* Change in condition Melting point/Melting range: Boiling point/Boiling range:	
*Flash point:	44°C
*Ignition temperature:	315°C
*Self-inflammability:	Product is not selfigniting.
*Danger of explosion:	Product is not explosive. However, formation of explosive ai vapor mixtures is possible.
* Critical values for explosion:	
Lower:	1.5 Vol %
Upper:	10.8 Vol %
*Vapor pressure at 20°C:	3.4 mbar
*Density at 20°C	1.0-1.4 g/cm3
* Solubility in / Miscibility with Water:	Not miscible or difficult to mix
* Solvent content: Organic solvents:	70-90 %
* Solids content:	10-30 %

10 Stability and reactivity

* Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

* Dangerous reactions No dangerous reactions known

* Dangerous products of decomposition: No dangerous decomposition products known

11 Toxicological information

- *Acute toxicity:
- *Primary irritant effect:

* on the skin: No irritant effect.

- * on the eye: Irritant effect.
- * Sensitization: No sensitizing effect known.
- *Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

(Contd. on page 4) GB

Material Safety Data Sheet

According to 91/155 EEC

Printing date 06.07.2006

Reviewed on 15.07.2005

Trade name: DECOMET 3108/10

(Contd. of page 3)

Irritant

12 Ecological information:

* General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

13 Disposal considerations

* Product:

*Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

*European waste catalogue

08 03 12 waste ink containing dangerous substances

* Uncleaned packagings:

* **Recommendation:** Disposal must be made according to official regulations.

*Land transport ADR/RIE) and GGVS/GGVE (cross-border/domestic)	
Č		
3		
*ADR/RID-GGVS/E Class		
*Kemler Number:	30	
* UN-Number:	3272	
*Packaging group:	<i>III</i>	
*Label	3	
	•	
* Proper shipping name:	3272 Esters, n.o.s. (2-methoxy-1-methylethyl acetate)	
* Proper shipping name: * Maritime transport IMDO	G/GGVSea:	
* Proper shipping name:		
* Proper shipping name: * Maritime transport IMDO * IMDG/GGVSea Class: * UN Number:	G/GGVSea:	
* Proper shipping name: * Maritime transport IMDO * IMDG/GGVSea Class: * UN Number: * Label	3 3272	
* Proper shipping name: * Maritime transport IMDO * IMDG/GGVSea Class: * UN Number:	3 3272 3 III	
* Proper shipping name: * Maritime transport IMDO * IMDG/GGVSea Class: * UN Number: * Label * Packaging group:	3 3272 3	

GB

Printing date 06.07.2006

Reviewed on 15.07.2005

	(Contd. of page
* Air transport ICAO-TI ai	nd IATA-DGR:
*ICAO/IATA Class: *UN/ID Number:	3 3272
*Label	3
*Packaging group:	<i>III</i>
* Proper shipping name:	ESTERS, N.O.S. (2-methoxy-1-methylethyl acetate)
5 Regulatory information	tion
b Regulatory information	
* Designation according	to EC quidelines:
The product has been c	lassified and labelled in accordance with EC Directives / Ordinance
The product has been c Hazardous Materials (Ge	lassified and labelled in accordance with EC Directives / Ordinance
Hazardous Materials (Ge * Code letter and hazard	lassified and labelled in accordance with EC Directives / Ordinance fStoffV)
Hazardous Materials (Ge	lassified and labelled in accordance with EC Directives / Ordinance fStoffV)
Hazardous Materials (Ge * Code letter and hazard Xi Irritant * Risk phrases:	lassified and labelled in accordance with EC Directives / Ordinance fStoffV)
Hazardous Materials (Ge * Code letter and hazard Xi Irritant * Risk phrases: 10 Flammable.	lassified and labelled in accordance with EC Directives / Ordinance fStoffV)
Hazardous Materials (Ge * Code letter and hazard Xi Irritant * Risk phrases: 10 Flammable. 36 Irritating to eyes.	lassified and labelled in accordance with EC Directives / Ordinance fStoffV)
Hazardous Materials (Ge * Code letter and hazard Xi Irritant * Risk phrases: 10 Flammable. 36 Irritating to eyes. * Safety phrases:	lassified and labelled in accordance with EC Directives / Ordinance fStoffV) designation of product:
Hazardous Materials (Ge * Code letter and hazard Xi Irritant * Risk phrases: 10 Flammable. 36 Irritating to eyes. * Safety phrases: 7/8 Keep container tightly	lassified and labelled in accordance with EC Directives / Ordinance fStoffV) designation of product: / closed and dry.
Hazardous Materials (Ge * Code letter and hazard Xi Irritant * Risk phrases: 10 Flammable. 36 Irritating to eyes. * Safety phrases: 7/8 Keep container tightly 25 Avoid contact with eye	lassified and labelled in accordance with EC Directives / Ordinance fStoffV) designation of product: / closed and dry.
Hazardous Materials (Ge * Code letter and hazard Xi Irritant * Risk phrases: 10 Flammable. 36 Irritating to eyes. * Safety phrases: 7/8 Keep container tightly 25 Avoid contact with eye * National regulations	lassified and labelled in accordance with EC Directives / Ordinance fStoffV) designation of product: / closed and dry. es.
Hazardous Materials (Ge * Code letter and hazard Xi Irritant * Risk phrases: 10 Flammable. 36 Irritating to eyes. * Safety phrases: 7/8 Keep container tightly 25 Avoid contact with eye * National regulations * Technical instructions (lassified and labelled in accordance with EC Directives / Ordinance fStoffV) designation of product: / closed and dry. es.
Hazardous Materials (Ge * Code letter and hazard Xi Irritant * Risk phrases: 10 Flammable. 36 Irritating to eyes. * Safety phrases: 7/8 Keep container tightly 25 Avoid contact with eye * National regulations * Technical instructions (Class Share in %	lassified and labelled in accordance with EC Directives / Ordinance fStoffV) designation of product: / closed and dry. es.
Hazardous Materials (Ge * Code letter and hazard Xi Irritant * Risk phrases: 10 Flammable. 36 Irritating to eyes. * Safety phrases: 7/8 Keep container tightly 25 Avoid contact with eye * National regulations * Technical instructions (lassified and labelled in accordance with EC Directives / Ordinance fStoffV) designation of product: / closed and dry. es.
Hazardous Materials (Ge * Code letter and hazard Xi Irritant * Risk phrases: 10 Flammable. 36 Irritating to eyes. * Safety phrases: 7/8 Keep container tightly 25 Avoid contact with eye * National regulations * Technical instructions (Class Share in % III 90.0	lassified and labelled in accordance with EC Directives / Ordinance fStoffV) designation of product: / closed and dry. es. (air):
Hazardous Materials (Ge * Code letter and hazard Xi Irritant * Risk phrases: 10 Flammable. 36 Irritating to eyes. * Safety phrases: 7/8 Keep container tightly 25 Avoid contact with eye * National regulations * Technical instructions (Class Share in % III 90.0	lassified and labelled in accordance with EC Directives / Ordinance fStoffV) designation of product: / closed and dry. es.
Hazardous Materials (Ge * Code letter and hazard Xi Irritant * Risk phrases: 10 Flammable. 36 Irritating to eyes. * Safety phrases: 7/8 Keep container tightly 25 Avoid contact with eye * National regulations * Technical instructions (Class Share in % III 90.0 * Water hazard class: Wa	lassified and labelled in accordance with EC Directives / Ordinance fStoffV) designation of product: / closed and dry. es. (air):
Hazardous Materials (Ge * Code letter and hazard Xi Irritant * Risk phrases: 10 Flammable. 36 Irritating to eyes. * Safety phrases: 7/8 Keep container tightly 25 Avoid contact with eye * National regulations * Technical instructions (Class Share in % III 90.0 * Water hazard class: Wa 6 Other information:	lassified and labelled in accordance with EC Directives / Ordinance fStoffV) designation of product: closed and dry.<br es.

10 Flammable.

15 Contact with water liberates extremely flammable gases. 36 Irritating to eyes.

* **Department issuing data specification sheet:** Department QSI * **Contact:** Dipl.-Ing.(FH) Milisterfer